



Type	ø D mm	Length L mm	Height H mm	Height H mm	Power kW	Weight kg	Connection flange			Sizes of feet				
							DL	X	ø B	L1	L2	B1	B2	B3
ESN 3 - 7,5	300	500	-	-	0,75	40	355	4	14	Without feet and/or on demand				
ESN 4 - 15	400	750	-	-	1,5	90	455	8	14	Without feet and/or on demand				
ESN 4 - 30	400	750	-	-	3,0	100	455	8	14	Without feet and/or on demand				
ESN 5 - 55	500	950	-	-	5,5	175	560	8	18	Without feet and/or on demand				
ESN 5 - 75	500	950	-	-	7,5	185	560	8	18	Without feet and/or on demand				
ESN 6 - 75	600	1000	-	-	7,5	210	660	12	18	Without feet and/or on demand				
ESN 6 - 110	600	1020	-	-	11,0	270	660	12	18	Without feet and/or on demand				
ESN 6 - 150	600	1020	-	-	15,0	295	660	12	18	Without feet and/or on demand				
ESN 7 - 220	700	1235	-	-	22,0	435	760	12	18	Without feet and/or on demand				
ESN 7 - 300	700	1235	-	-	30,0	480	760	12	18	Without feet and/or on demand				
ESN 8 - 300	800	1400	-	-	30,0	500	860	12	18	Without feet and/or on demand				
ESN 8 - 370	800	1400	-	-	37,0	525	860	12	18	Without feet and/or on demand				
ESN 8 - 450	800	1400	-	-	45,0	590	860	12	18	Without feet and/or on demand				
ESN 9 - 220	900	1300	1060	555	22,0	620	960	16	18	95	590	600	900	1000
ESN 9 - 300	900	1300	1060	555	30,0	630	960	16	18	95	590	600	900	1000
ESN 9 - 370	900	1630	1155	650	37,0	785	960	16	18	100	780	600	900	1000
ESN 9 - 450	900	1350	1155	650	45,0	800	960	16	18	100	630	600	900	1000
ESN 9 - 550	900	1630	1155	650	55,0	980	960	16	18	100	780	600	900	1000
ESN 9 - 750	900	1630	1155	650	75,0	1160	960	16	18	100	780	600	900	1000

Pole-changing and/or individually adjustable on demand